



B 200

rolamento ESFÉRICO
fixação por PARAFUSOS
serviço LEVE



Rolamento	Eixo		Dimensão nominal (mm)						ds (mm) (UNF)	Cargas (Kgf)		Peso (Kg)
	Ø pol	Ø mm	D	Bi	n	m	Be	G		dinâmica C _r	estática C _{or}	
B 201 V22 B 201-8 V22	1/2	12	40,0	22,0	6,0	16,0	12,0	4,0	M5x0,8 10-32	970	490	0,10
B 202 V22 B 202-10 V22	5/8	15	40,0	22,0	6,0	16,0	12,0	4,0	M5x0,8 10-32	970	490	0,10
B 203 V22		17	40,0	22,0	6,0	16,0	12,0	4,0	M5x0,8 10-32	970	490	0,10
B 204-12 V22 B 204 V22	3/4	20	47,0	25,0	7,0	18,0	14,0	5,0	M6x1 1/4-28	1310	680	0,15
B 205 V22 B 205-16 V22	1	25	52,0	27,0	7,5	19,5	15,0	5,5	M6x1 1/4-28	1430	800	0,20
B 206 V22 B 206-20 V22	1-1/4	30	62,0	29,0	8,0	21,0	16,0	6,0	M6x1 1/4-28	2000	1140	0,20
B 207-20 V22 B 207 V22 B 207-23 V22 B 207-400 V22	1-1/4 1-7/16	35 40	72,0	35,0	9,5	25,5	19,0	6,0	M6x1 1/4-28	2640	1550	0,40
B 208-24 V22 B 208 V22	1-1/2	40	80,0	39,5	10,5	29,0	21,0	7,0	M8x1 5/16-24	2990	1860	0,50
B 209 V22		45	85,0	41,5	11,0	30,5	22,0	8,0	M8x1	3550	2120	0,68
B 210 V22		50	90,0	43,0	11,0	32,0	22,0	9,0	M10x1,25	3600	2370	0,80
B 211 V22		55	100,0	45,0	13,0	32,0	24,0	9,0	M10x1,25	4400	2980	1,00
B 212 V22		60	110,0	47,0	13,0	34,0	24,0	10,0	M10x1,25	5350	3350	1,30