



SSY 200

AÇO INOXIDÁVEL
 rolamento ESFÉRICO
 fixação por PARAFUSOS
 serviço NORMAL



Rolamento	Eixo		Dimensão nominal (mm)							ds (mm) (UNF)	Cargas (Kgf)		Peso (Kg)	Rotação Máxima (rpm) Ajuste h7
	Série SSY	Ø pol	Ø mm	D	d1	Bi	n	m	Be		G	dinâmica C _r		
SSY 204-12 V22 SSY 204 V22	3/4	20	47,0	29,0	31,0	12,7	18,3	17,0	5,0	M6x1 1/4-28	990	665	0,20	4800
SSY 205-14 V22 SSY 205 V22 SSY 205-16 V22	7/8 1													
SSY 206-18 V22 SSY 206 V22 SSY 206-19 V22 SSY 206-20 V22	1-1/8 1-3/16 1-1/4	30	62,0	40,5	38,1	15,9	22,2	19,0	5,0	M6x1 1/4-28	1500	1120	0,30	3400
SSY 207-20 V22 SSY 207 V22 SSY 207-23 V22	1-1/4 1-7/16													
SSY 208-24 V22 SSY 208 V22	1-1/2 40	40	80,0	53,0	49,2	19,0	30,2	21,0	8,0	M8x1 5/16-24	2230	1820	0,65	2600
SSY 209-27 V22 SSY 209-28 V22 SSY 209 V22	1-11/16 1-3/4 45													
SSY 210-31 V22 SSY 210 V22 SSY 210-32 V22	1-15/16 2	50	90,0	62,0	51,6	19,0	32,6	24,0	10,0	M10x1,25 3/8-24	2690	2320	0,80	2200
SSY 211-32 V22 SSY 211 V22 SSY 211-35 V22	2 2-3/16													
SSY 212 V22 SSY 212-39 V22	60 2-7/16	60	110,0	75,0	65,1	25,4	39,7	27,0	10,0	M10x1,25 3/8-24	4020	3280	1,55	1800
SSY 213 V22	65													
SSY 214 V22	70	70	125,0	86,5	74,6	30,2	44,4	30,0	12,0	M12x1,25	4760	4500	2,00	1600
SSY 215 V22 SSY 215-48 V22	75 3													
SSY 216 V22 SSY 216-51 V22	80 3-3/16	80	140,0	98,0	82,6	33,3	49,3	33,0	14,0	M12x1,25	5550	5420	2,80	1400
SSY 217 V22 SSY 217-55 V22	85 3-7/16													
SSY 218 V22	90	90	160,0	111,0	96,0	39,7	56,3	37,0	14,0	M12x1,25	7310	7150	4,50	1200