




GE(00)FO GE(00)FO 2RS

serviço PESADO
contato AÇO/AÇO
RELUBRIFICÁVEL



GE(00)FO 2RS
dimensões de montagem



Rolamento de rótula		Eixo (mm) d	Dimensão nominal (mm)					Dimensão de montagem (mm)		Peso (kg)	Cargas (kgf)		Folga radial interna CN		
			D	Bi	Be	dk	α	r1 (min.)	r2 (min.)		da (máx.)	Da (min.)		dinâmica Cr	estática Cor
GE6FO	-	6	16	9	5	13,0 ¹⁾	21°	0,3	0,3	9,3	12,5	0,008	561	2804	0,032 - 0,068
GE8FO	-	8	19	11	6	16,0 ¹⁾	21°	0,3	0,3	11,6	15,5	0,014	831	4130	0,032 - 0,068
GE10FO	-	10	22	12	7	18,0 ¹⁾	18°	0,3	0,3	13,4	17,5	0,020	1101	5506	0,032 - 0,068
GE12FO	-	12	26	15	9	22,0 ¹⁾	18°	0,3	0,3	16,0	21,0	0,034	1734	8668	0,040 - 0,082
-	GE15FO 2RS	15	30	16	10	25,0 ¹⁾	16°	0,3	0,3	19,2	24,0	0,046	2162	10809	0,040 - 0,082
-	GE17FO 2RS	17	35	20	12	29,0 ¹⁾	19°	0,3	0,3	21,0	27,5	0,077	3059	14888	0,040 - 0,082
-	GE20FO 2RS	20	42	25	16	35,5	17°	0,3	0,6	25,2	33,0	0,150	4895	24473	0,050 - 0,100
-	GE25FO 2RS	25	47	28	18	40,7	17°	0,6	0,6	29,5	38,0	0,190	6322	31611	0,050 - 0,100
-	GE30FO 2RS	30	55	32	20	47,0	17°	0,6	1,0	34,4	44,5	0,290	8158	40789	0,050 - 0,100
-	GE35FO 2RS	35	62	35	22	53,0	16°	0,6	1,0	39,7	51,0	0,380	10197	50986	0,060 - 0,120
-	GE40FO 2RS	40	68	40	25	60,0	17°	0,6	1,0	44,7	57,0	0,540	12950	65262	0,060 - 0,120
-	GE45FO 2RS	45	75	43	28	66,0	15°	0,6	1,0	50,0	63,0	0,680	15908	79538	0,060 - 0,120
-	GE50FO 2RS	50	90	56	36	80,0	17°	0,6	1,0	57,1	75,0	1,400	24983	124406	0,060 - 0,120
-	GE60FO 2RS	60	105	63	40	92,0	17°	1,0	1,0	67,0	87,0	2,000	32121	159076	0,072 - 0,142
-	GE70FO 2RS	70	120	70	45	105,0	16°	1,0	1,0	78,2	99,0	2,900	40789	203944	0,072 - 0,142
-	GE80FO 2RS	80	130	75	50	115,0	14°	1,0	1,0	87,1	108,0	3,500	49966	249831	0,072 - 0,142
-	GE90FO 2RS	90	150	85	55	130,0	15°	1,0	1,0	98,3	123,0	5,400	62203	311015	0,085 - 0,165
-	GE100FO 2RS	100	160	85	55	140,0	14°	1,0	1,0	111,2	134,0	5,900	66792	331409	0,085 - 0,165
-	GE110FO 2RS	110	180	100	70	160,0	12°	1,0	1,0	124,8	150,0	9,600	96873	484367	0,085 - 0,165
-	GE120FO 2RS	120	210	115	70	180,0	16°	1,0	1,0	138,4	173,0	15,100	110130	550649	0,085 - 0,165
-	GE140FO 2RS	140	230	130	80	200,0	16°	1,0	1,0	151,9	191,0	18,800	139702	693410	0,100 - 0,192
-	GE160FO 2RS	160	260	135	80	225,0	16°	1,0	1,1	180,0	219,0	24,700	156017	780086	0,100 - 0,192
-	GE180FO 2RS	180	290	155	100	250,0	14°	1,1	1,1	196,1	239,0	35,400	216181	1080903	0,100 - 0,192
-	GE200FO 2RS	200	320	165	100	275,0	15°	1,1	1,1	220,0	267,0	44,800	236575	1182875	0,110 - 0,214
-	GE220FO 2RS	220	340	175	100	300,0	16°	1,1	1,1	243,6	295,0	50,900	260029	1295044	0,110 - 0,214
-	GE240FO 2RS	240	370	190	110	325,0	15°	1,1	1,1	263,6	319,0	64,900	311015	1560172	0,125 - 0,239
-	GE260FO 2RS	260	400	205	120	350,0	15°	1,1	1,1	283,6	342,0	81,700	362001	1835496	0,125 - 0,239
-	GE280FO 2RS	280	430	210	120	375,0	15°	1,1	1,1	310,6	370,0	96,500	387494	1937468	0,125 - 0,239

¹⁾ - não possui canal de lubrificação no anel interno