



Caixa	Eixo		Dimensão nominal (mm)								Paraf.
	Ø pol	Ø mm	h	a	e	b	s1	s2	g	w	
MP 25	1	25	44,5	159	119,0	51,0	14	25	16,0	87,5	M12 1/2
MP 30	1-3/16 1-1/4	30	47,6	166	129,5	46,6	14	25	17,5	92,6	M12 1/2
MP 35	1-3/8 1-7/16	35	54,0	203	145,0	57,0	14	30	19,0	106,4	M12 1/2
MP 40	1-1/2	40	58,7	222	155,0	66,0	18	32	20,5	116	M16 5/8
MP 45	1-3/4 1-11/16	45	58,7	222	156,0	66,0	18	33	20,5	117,5	M16 5/8
MP 50	1-7/8 1-15/16 2	50	63,5	241	171,5	73,0	18	36	22,0	129,4	M16 5/8
MP 55	2-3/16 2-1/4	55	69,8	260	183,5	79,0	22	36	27,0	142,9	M20 3/4
MP 60 MP 65	2-7/16 2-1/2	60 65	76,2	286	203,0	83,0	22	41	27,0	158,7	M20 3/4
MP 65 MP 70	2-11/16 2-3/4	65 70	88,9	330	229,0	89,0	24	51	28,5	177,8	M22 7/8
MP 75	2-15/16 3	75	88,9	330	229,0	89,0	24	51	32,0	184,1	M22 7/8
MP 80	3-3/16 3-1/4	80	101,6	381	282,0	102,0	24	59	32,0	203,3	M22 7/8
MP 85 MP 90	3-7/16 3-1/2	85 90	101,6	381	283,0	111,0	24	59	33,0	209,5	M22 7/8
MP 95 MP 100	3-15/16	95 100	127,0	432	336,5	120,0	26	64	33,0	254	M24 1

Peso (kg) YMP00 UCXMP00	D	Rolamentos Y200 / UCX 00 <sup>(1)</sup>	
		Bi1	m1
1,10	62,0	38,1	22,2
1,40	72,0	42,9	25,4
1,80	80,0	49,2	30,2
3,40	85,0	49,2	30,2
3,60	90,0	51,6	32,6
4,50	100,0	55,6	33,4
5,90	110,0	65,1	39,7
8,30	125,0	74,6	44,4
11,10	130,0	77,8	44,5
12,00	140,0	82,6	49,3
15,10	150,0	85,7	51,6
19,50	160,0	96,0	56,3
28,60	200,0	103,0	62

(1) - para escolha do eixo considerar o diâmetro externo da série (D)