



C 300

mancal tipo CARTUCHO
serviço PESADO



Caixa	Eixo		Dimensão nominal (mm)			Peso (Kg)			D	Rolamentos							
	Ø pol	Ø mm	a	l	r	YC3	UGC3	UKC3		Y 300		UG 300 / G 300		UK300			
									Bi1	m1	Bi2	m2	Ø Eixo	Bucha	Bi3	m3	
C 305	1	25	90,0	26,0	2,5	1,10	1,10	1,20	62,0	38,0	23,0	46,8	30,1	3/4 20	HE2305 H2305	35,0	21,5
C 306	1-3/16	30	100,0	28,0	2,5	1,40	1,50	1,40	72,0	43,0	26,0	50,0	32,5	7/8 15/16 25 1	HS2306 HA2306 H2306 HE2306	38,0	23,0
C 307	1-1/4 1-7/16	35	110,0	32,0	3,0	1,80	1,80	1,80	80,0	48,0	29,0	51,6	33,3	1-1/8 30 1-3/16	HS2307 H2307 HA2307	43,0	25,5
C 308	1-1/2	40	120,0	34,0	3,0	2,20	2,30	2,20	90,0	52,0	33,0	57,1	37,3	1-1/4 1-5/16 1-3/8 35	HE2308 HA2308 HS2308 H2308	46,0	27,5
C 309	1-11/16 1-3/4	45	130,0	38,0	3,5	2,70	2,90	2,80	100,0	57,0	35,0	58,7	38,9	1-7/16 1-1/2 40 1-5/8	HA2309 HE2309 H2309 HS2309	50,0	30,0
C 310	1-7/8 1-15/16	50	140,0	40,0	3,5	3,30	3,50	3,30	110,0	61,0	39,0	66,6	42,0	1-11/16 1-3/4 45	HA2310 HE2310 H2310	55,0	32,0
C 311	2 2-1/8 2-3/16	55	150,0	44,0	3,5	3,90	4,20	3,90	120,0	66,0	40,0	73,0	45,2	1-7/8 1-15/16 50 2	HS2311 HA2311 H2311 HE2311	59,0	33,5
C 312	2-1/4 2-3/8 2-7/16	60	160,0	46,0	3,5	4,80	5,10	4,70	130,0	71,0	43,0	79,4	48,5	2-1/8 55	HS2312 H2312	62,0	36,5
C 313	2-1/2	65	170,0	50,0	3,5	5,80	6,20	5,60	140,0	75,0	45,0	85,7	53,2	2-3/16 2-1/4 60 2-3/8	HA2313 HE2313 H2313 HS2313	65,0	38,5
C 314	2-11/16	70	180,0	52,0	4,0	6,60	7,20	-	150,0	78,0	47,0	92,1	58,0	-	-	-	-
C 315	2-15/16 3	75	190,0	55,0	4,0	7,80	8,40	7,90	160,0	82,0	50,0	100,0	62,7	2-1/2 65	HE2315 H2315	73,0	42,5
C 316	3-3/16	80	200,0	60,0	4,0	9,00	10,00	9,20	170,0	86,0	52,0	106,4	65,9	2-3/4 70	HE2316 H2316	78,0	44,5
C 317		85	215,0	64,0	4,0	11,00	13,00	11,00	180,0	96,0	56,0	109,5	67,5	75 3	H2317 HE2317	82,0	48,0

Caixa	Eixo		Dimensão nominal (mm)			Peso (Kg)			D	Rolamentos							
	Ø pol	Ø mm	a	l	r	YC3	UGC3	UKC3		Y 300		UG 300 / G 300		UK300			
									Bi1	m1	Bi2	m2	Ø Eixo	Bucha	Bi3	m3	
C 318	3-7/16	90	225,0	66,0	4,0	12,00	14,00	13,00	190,0	96,0	56,0	115,9	72,3	80	H2318	86,0	48,0
C 319		95 100	240,0	72,0	4,0	15,00	17,00	16,00	200,0	103,0	62,0	122,3	83,4	3-1/4 85	HE2319 H2319	90,0	52,0
C 320	3-15/16 4	100	260,0	75,0	4,0	19,00	21,00	20,00	215,0	108,0	66,0	128,6	78,6	3-1/2 90	HE2320 H2320	97,0	54,0
C 322		110	300,0	80,0	5,0	28,00	31,20	29,00	240,0	117,0	71,0	141,3	92,1	100 4	H2322 HE2322	105,0	61,0
C 324		120	320,0	90,0	5,0	35,00	-	35,00	260,0	126,0	75,0	-	-	110	H2324	112,0	65,5
C 326		130	340,0	100,0	5,0	42,00	-	43,00	280,0	135,0	81,0	-	-	115	H2326	121,0	68,0
C 328		140	360,0	100,0	5,0	49,00	-	49,00	300,0	145,0	86,0	-	-	125	H2328	131,0	73,0