



GA(00)UK GAL(00)UK

rosca EXTERNA
serviço MÉDIO
contato AÇO/PTFE
LUBRIFICAÇÃO PERMANENTE



Terminal de rótula		Eixo (mm) d	Dimensão nominal (mm)											Peso (kg)	Cargas (kgf)		Folga radial interna CN
Rosca direita	Rosca esquerda		D	Bi	dk	d1	a	s	h	Be	α	r	w		dinâmica C_r	estática C_{or}	
GA6UK	GAL6UK	6	14	6	10,0	8,0	21	M6x1	36	4,4	13°	18	46,5	0,017	367	1040	0 – 0,032
GA8UK	GAL8UK	8	16	8	13,0	10,2	24	M8x1,25	42	6,0	15°	22	54,0	0,029	597	1632	0 – 0,032
GA10UK	GAL10UK	10	19	9	16,0	13,2	29	M10x1,5	48	7,0	12°	26	62,5	0,051	882	2243	0 – 0,032
GA12UK	GAL12UK	12	22	10	18,0	14,9	34	M12x1,75	54	8,0	11°	28	71,0	0,086	1162	3100	0 – 0,032
GA15UK	GAL15UK	15	26	12	22,0	18,4	40	M14x2	63	10,0	8°	34	83,0	0,140	1795	4568	0 – 0,040
GA17UK	GAL17UK	17	30	14	25,0	20,7	46	M16x2	69	11,0	10°	36	92,0	0,190	2284	5761	0 – 0,040
GA20UK	GAL20UK	20	35	16	29,0	24,1	53	MF20x1,5	78	13,0	9°	43	104,5	0,310	3212	7709	0 – 0,040
GA25UK	GAL25UK	25	42	20	35,5	29,3	64	MF24x2	94	17,0	7°	53	126,0	0,560	5201	10605	0 – 0,050
GA30UK	GAL30UK	30	47	22	40,7	34,2	73	MF30x2	110	19,0	6°	65	146,5	0,890	6679	14072	0 – 0,050

