



- Vedação opcional: TS.



| Eixo Ød mm | Caixa | Montagem | | | | Cargas (kgf) | | Limite Rotação RPM | Dimensão nominal (mm) | | | | | | | | | | | | | Paraf. | Peso (kg) | |
|------------------|-----------|-----------|---------------------|---------------------|---------------|----------------------------|-----------------------------|--------------------------|-----------------------|-----|-----|-----|-----|-----|----|----|----|-----|-----|-----|-----|--------|--------------|-------|
| | | Rolamento | Bucha de Fixação | Anel de Bloqueio | Tampa Cega | dinâmica C _r | estática C _{0r} | | h | a | e | b1 | b2 | b3 | s1 | s2 | g | w | l | Ca | Da | | | t |
| 110 | SNLN 3024 | 23024K | H3024 | 1 FRB 10/180 | ATS 3024 | 35500 | 51000 | 4000 | 112,0 | 380 | 320 | 100 | 75 | 110 | 28 | 36 | 40 | 215 | 150 | 56 | 180 | 48 | M24 | 19,2 |
| 115 | SNLN 3026 | 23026K | H3026 | 1 FRB 10/200 | ATS 3026 | 43000 | 61000 | 3600 | 125,0 | 410 | 350 | 110 | 80 | 120 | 28 | 36 | 45 | 239 | 160 | 62 | 200 | 52 | M24 | 23,0 |
| 125 | SNLN 3028 | 23028K | H3028 | 1 FRB 10/210 | ATS 3028 | 46500 | 68000 | 3400 | 140,0 | 410 | 350 | 110 | 80 | 120 | 28 | 36 | 45 | 260 | 170 | 63 | 210 | 54 | M24 | 28,8 |
| 135 | SNLN 3030 | 23030K | H3030 | 1 FRB 10/225 | ATS 3030 | 51000 | 75000 | 3200 | 150,0 | 445 | 380 | 115 | 85 | 130 | 28 | 36 | 50 | 286 | 180 | 66 | 225 | 57 | M24 | 38,4 |
| 140 | SNLN 3032 | 23032K | H3032 | 1 FRB 10/240 | AL 520 | 58500 | 88000 | 3000 | 150,0 | 460 | 390 | 115 | 85 | 130 | 28 | 36 | 50 | 297 | 190 | 70 | 240 | 61 | M24 | 39,4 |
| 150 | SNLN 3034 | 23034K | H3034 | 1 FRB 10/260 | AL 522 | 71000 | 106000 | 2800 | 160,0 | 530 | 450 | 145 | 100 | 160 | 35 | 48 | 60 | 318 | 205 | 77 | 260 | 66 | M30 | 53,9 |
| 160 | SNLN 3036 | 23036K | H3036 | 1 FRB 10/280 | AL 524 | 83000 | 125000 | 2600 | 170,0 | 550 | 470 | 150 | 105 | 160 | 35 | 48 | 60 | 338 | 210 | 84 | 280 | 70 | M30 | 59,5 |
| 170 | SNLN 3038 | 23038K | H3038 | 1 FRB 10/290 | AL 526 | 86500 | 134000 | 2400 | 170,0 | 550 | 470 | 150 | 105 | 160 | 35 | 48 | 60 | 346 | 220 | 85 | 290 | 72 | M30 | 67,2 |
| 180 | SNLN 3040 | 23040K | H3040 | 1 FRB 10/310 | AL 528 | 100000 | 153000 | 2200 | 180,0 | 610 | 515 | 160 | 110 | 170 | 35 | 48 | 60 | 366 | 235 | 92 | 310 | 77 | M30 | 76,8 |
| 200 | SNLN 3044 | 23044K | OH3044H | 1 FRB 10/340 | ATS 3044 | 122000 | 186000 | 2000 | 200,0 | 690 | 580 | 170 | 115 | 190 | 42 | 50 | 70 | 401 | 255 | 100 | 340 | 80 | M36 | 100,8 |
| 220 | SNLN 3048 | 23048K | OH3048H | 1 FRB 10/360 | ATS 3048 | 129000 | 208000 | 1900 | 210,0 | 720 | 610 | 190 | 130 | 200 | 42 | 50 | 75 | 422 | 265 | 102 | 360 | 85 | M36 | 120,0 |
| 240 | SNLN 3052 | 23052K | OH3052H | 1 FRB 10/400 | ATS 3052 | 160000 | 255000 | 1700 | 240,0 | 820 | 680 | 200 | 130 | 220 | 48 | 70 | 80 | 472 | 285 | 114 | 400 | 91 | M42 | 153,6 |
| 260 | SNLN 3056 | 23056K | OH3056H | 1 FRB 10/420 | ATS 3056 | 173000 | 285000 | 1600 | 250,0 | 860 | 720 | 210 | 140 | 230 | 48 | 70 | 80 | 495 | 295 | 116 | 420 | 96 | M42 | 172,8 |

Esta linha permite montagens para eixos com diâmetros em polegadas.
Consulte os Departamentos de Engenharia / Comercial da FRM para verificar as medidas disponíveis e especificar os componentes.