



SC 200

mancal tipo CARTUCHO
serviço NORMAL



Caixa	Eixo		Dimensão nominal (mm)			Peso (kg) YSC2 YSC2T	D	Rolamentos Y 200 / Y 200 T		
	Ø pol	Ø mm	a	l	r			Bi	m	
SC 203	1/2 5/8	12	68,2	22,2	1,5	0,45	47,0	31,0	18,3	
		15								
		17								
SC 204	3/4	20	74,6	22,2	1,5	0,45	47,0	31,0	18,3	
SC 205	7/8 15/16 1	25	79,3	26,2	1,5	0,50	52,0	34,0	19,7	
										1-1/16
SC 206	1-1/8 1-3/16 1-1/4	30	88,9	27,7	2,0	0,50	62,0	38,1	22,2	
										1-1/4
										1-5/16
SC 207	1-3/8 1-7/16	35	98,4	31,0	2,0	0,70	72,0	42,9	25,4	
										1-1/2
										1-5/8
SC 208	1-11/16 1-3/4	45	111,1	36,5	2,5	1,10	85,0	49,2	30,2	
										1-13/16
										1-7/8
SC 210	1-15/16 2	50	115,9	37,3	2,5	1,10	90,0	51,6	32,6	
										2
										2-1/8
SC 211	2-3/16	55	125,4	40,5	2,5	1,50	100,0	55,6	33,4	
										2-1/4
SC 212	2-7/16	60	149,2	41,3	2,5	2,00	110,0	65,1	39,7	
SC 214	2-3/4	70	158,7	50,8	3,0	2,50	125,0	74,6	44,4	
SC 215	2-15/16 3	75	168,3	50,8	3,0	2,60	130,0	77,8	44,5	
SC 216	3-3/16	80	177,8	55,5	3,5	3,10	140,0	82,6	49,3	
SC 217	3-1/4	85	188,9	63,5	3,5	3,60	150,0	85,7	51,6	
SC 218	3-1/2	90	208,0	63,5	4,0	3,90	160,0	96,0	56,3	