



GAK(00)PB GAKL(00)PB

rosca EXTERNA
serviço LEVE
contato AÇO/BRONZE
RELUBRIFICÁVEL



Terminal de rótula		Eixo (mm)	Dimensão nominal (mm)											Peso (kg)	Cargas (kgf)		Folga radial interna CN
Rosca direita	Rosca esquerda		d	D	Bi	dk	d1	a	s	h	Be	α	r		w	dinâmica C_r	
GAK5PB	GAKL5PB	5	13	8	11,112	7,7	18	M5x0,8	33	6,0	13°	19	42	0,013	331	499	0 – 0,035
GAK6PB	GAKL6PB	6	16	9	12,700	8,9	20	M6x1	36	6,8	13°	21	46	0,020	438	706	0 – 0,035
GAK8PB	GAKL8PB	8	19	12	15,875	10,3	24	M8x1,25	42	9,0	14°	25	54	0,038	734	1315	0 – 0,035
GAK10PB	GAKL10PB	10	22	14	19,050	12,9	28	M10x1,5	48	10,5	13°	28	62	0,055	1020	1886	0 – 0,035
GAK12PB	GAKL12PB	12	26	16	22,225	15,4	32	M12x1,75	54	12,0	13°	32	70	0,085	1366	2121	0 – 0,035
GAK14PB	GAKL14PB	14	28	19	25,400	16,8	36	M14x2	60	13,5	16°	36	78	0,140	1734	3263	0 – 0,035
GAK16PB	GAKL16PB	16	32	21	28,575	19,3	42	M16x2	66	15,0	15°	37	87	0,210	2203	4609	0 – 0,035
GAK18PB	GAKL18PB	18	35	23	31,750	21,8	46	MF18x1,5	72	16,5	15°	41	95	0,280	2651	4782	0 – 0,035
GAK20PB	GAKL20PB	20	40	25	34,925	24,3	50	MF20x1,5	78	18,0	14°	45	103	0,380	3212	4650	0 – 0,035
GAK22PB	GAKL22PB	22	42	28	38,100	25,8	54	MF22x1,5	84	20,0	15°	48	111	0,480	3875	6230	0 – 0,035
GAK25PB	GAKL25PB	25	47	31	42,850	29,5	60	MF24x2	94	22,0	15°	55	124	0,640	4844	7424	0 – 0,035
GAK30PB	GAKL30PB	30	55	37	50,800	34,8	70	MF30x2	110	25,0	17°	66	145	1,100	6526	9779	0 – 0,035

