



Eixo Ød mm	Mancal	Montagem			Cargas (kgf)		Limite Rotação RPM	Dimensão nominal (mm)														Paraf.	Peso (kg)	
		Rolamento	Bucha de Fixação	Anel de Bloqueio	dinâmica C _r	estática C _{or}		h	a	e	e1	b	s1	s2	g	w	l1	l2	Ca	Da	o			t
150	SNL 3134	23134K	H3134	2 FRB 10/280	104000	150000	2400	170,0	510	430	100	180	28	34	70	333	229	240	108	280	14	78	M24	77,7
160	SNL 3136	23136K	H3136	2 FRB 10/300	120000	176000	2200	180,0	530	450	110	190	28	34	75	353	239	250	116	300	15	83	M24	87,4
170	SNL 3138	23138K	H3138	2 FRB 10/320	137000	208000	2000	190,0	560	480	120	210	28	34	80	375	260	270	124	320	10	88	M24	102,8
180	SNL 3140	23140K	H3140	2 FRB 10/340	160000	236000	1900	210,0	610	510	130	230	35	42	85	411	280	290	132	340	10	93	M30	126,7
200	SNL 3144	23144K	OH3144H	2 FRB 10/370	180000	275000	1700	220,0	640	540	140	240	35	42	90	434	290	300	140	370	12	100	M30	144,0
220	SNL 3148	23148K	OH3148H	2 FRB 10/400	208000	320000	1600	240,0	700	600	150	260	35	42	95	474	310	315	148	400	12	106	M30	185,7
240	SNL 3152	23152K	OH3152H	2 FRB 10/440	255000	390000	1400	260,0	770	650	160	280	42	50	100	516	320	330	164	440	13	116	M36	221,0
260	SNL 3156	23156K	OH3156H	2 FRB 10/460	265000	425000	1300	280,0	790	670	160	280	42	50	105	551	320	330	166	460	16	119	M36	247,6
280	SNL 3160	23160K	OH3160H	2 FRB 10/500	320000	510000	1200	300,0	830	710	190	310	42	50	110	591	350	360	180	500	22	138	M36	315,0
300	SNL 3164	23164K	OH3164H	2 FRB 10/540	375000	600000	1100	320,0	880	750	200	330	42	50	115	631	370	380	196	540	23	149	M36	346,5

Esta linha permite montagens para eixos com diâmetros em polegadas.
 Consulte os Departamentos de Engenharia / Comercial da FRM para verificar as medidas disponíveis e especificar os componentes.

