



SNL 30C

Eixo Ød mm	Mancal	Montagem		Cargas (kgf)		Limite Rotação RPM	Dimensão nominal (mm)																Paraf.	Peso (kg)
		Rolamento	Anel de Bloqueio	dinâmica C _r	estática C _{0r}		h	a	e	e1	b	s1	s2	g	w	l1	l2	Ca	Da	o	t	d2		
180	SNL 3036 C	23036	2 FRB 17/280	83000	125000	2600	170,0	510	430	100	180	28	34	70	333	229	240	108	280	14	72	200	M24	76,9
190	SNL 3038 C	23038	4 FRB 10/290	86500	134000	2400	180,0	530	450	110	190	28	34	75	353	239	246,5	115	290	15	73	200	M24	80,0
200	SNL 3040 C	23040	4 FRB 10/310	100000	153000	2200	190,0	560	480	120	210	28	34	80	375	260	270	122	310	10	78	220	M24	100,7
220	SNL 3044 C	23044	4 FRB 10/340	122000	186000	2000	210,0	610	510	130	230	35	42	85	411	280	290	130	340	10	91	240	M30	127,0
240	SNL 3048 C	23048	4 FRB 12/360	129000	208000	1900	220,0	640	540	140	240	35	42	90	434	290	300	140	360	12	97	260	M30	144,0
260	SNL 3052 C	23052	2 FRB 22/400	160000	255000	1700	240,0	700	600	150	260	35	42	95	474	310	315	148	400	12	103	280	M30	191,0
280	SNL 3056 C	23056	6 FRB 10/420	173000	285000	1600	260,0	770	650	160	280	42	50	100	516	320	330	166	420	13	108	300	M36	227,3
300	SNL 3060 C	23060	2 FRB 25/460	212000	345000	1500	280,0	790	670	160	280	42	50	105	551	320	330	168	460	16	118	320	M36	264,6
320	SNL 3064 C	23064	6 FRB 10/480	224000	380000	1400	300,0	830	710	190	310	42	50	110	591	350	360	181	480	22	121	340	M36	318,0
340	SNL 3068 C	23068	4 FRB 16/520	270000	455000	1300	320,0	880	750	200	330	42	50	115	631	370	380	197	520	23	130	370	M36	348,5
360	SNL 3072 C	23072	4 FRB 16/540	275000	480000	1200	320,0	880	750	200	330	42	50	115	631	370	380	198	540	23	130	390	M36	350,5

