



# SNL 31C

Eixo Ød mm	Mancal	Montagem		Cargas (kgf)		Limite Rotação RPM	Dimensão nominal (mm)																Paraf.	Peso (kg)
		Rolamento	Anel de Bloqueio	dinâmica C <sub>r</sub>	estática C <sub>or</sub>		h	a	e	e1	b	s1	s2	g	w	l1	l2	Ca	Da	o	t	d2		
170	SNL 3134 C	23134	2 FRB 10/280	104000	150000	2400	170,0	510	430	100	180	28	34	70	333	229	240	108	280	14	78	180	M24	82,0
180	SNL 3136 C	23136	2 FRB 10/300	120000	176000	2200	180,0	530	450	110	190	28	34	75	353	239	250	116	300	15	83	200	M24	92,6
190	SNL 3138 C	23138	2 FRB 10/320	137000	208000	2000	190,0	560	480	120	210	28	34	80	375	260	270	124	320	10	88	200	M24	108,7
200	SNL 3140 C	23140	2 FRB 10/340	160000	236000	1900	210,0	610	510	130	230	35	42	85	411	280	290	132	340	10	93	220	M30	134,3
220	SNL 3144 C	23144	2 FRB 10/370	180000	275000	1700	220,0	640	540	140	240	35	42	42	434	290	300	140	370	12	100	240	M30	152,7
240	SNL 3148 C	23148	2 FRB 10/400	208000	320000	1600	240,0	700	600	150	260	35	42	95	474	310	315	148	400	12	106	260	M30	196,8
260	SNL 3152 C	23152	2 FRB 10/440	255000	390000	1400	260,0	770	650	160	280	42	50	100	516	320	330	164	440	13	116	280	M36	234,0
280	SNL 3156 C	23156	2 FRB 10/460	265000	425000	1300	280,0	790	670	160	280	42	50	105	551	320	330	166	460	16	119	300	M36	262,4
300	SNL 3160 C	23160	2 FRB 10/500	320000	510000	1200	300,0	830	710	190	310	42	50	110	591	350	360	180	500	22	138	320	M36	334,0
320	SNL 3164 C	23164	2 FRB 10/540	375000	600000	1100	320,0	880	750	200	330	42	50	115	631	370	380	196	540	23	149	340	M36	367,0

