



SOFN 200

Eixo Ød mm	Mancal	Montagem			Cargas (kgf)		Limite Rotação RPM	Dimensão nominal (mm)																	Roscas			Paraf.	Olhal	C (óleo)		Peso (kg)		
		Rolamento	Porca	Arruela	dinâmica C _r	estática C _{or}		h	a	e	e1	b	s1	s2	g	w	l	l1	l2	Ca	Da	d1	d2	x	Ga	Gb	Rg			p1	p2		nível min	nível máx
60	SOFN 212	22212	KM12	MB12	15600	16600	7500	95,0	270	210	50	92	19	30	30	168	145	75	68	34	110	58	68	3	M60x2	17	1/2 NPT	1/2 NPT	3/8 BSP	M16	M10	33	53	19,6
65	SOFN 213	22213	KM13	MB13	19300	21600	7000	100,0	290	233	50	95	19	33	30	180	148	78	70	37	120	63	75	3	M65x2	17	1/2 NPT	1/2 NPT	3/8 BSP	M16	M10	37	53	20,6
75	SOFN 215	22215	KM15	MB15	21200	24000	6300	110,0	290	230	55	100	19	34	30	198	152	85	78	41	130	73	80	5	M75x2	19	1/2 NPT	1/2 NPT	3/8 BSP	M16	M10	40	60	21,6
85	SOFN 217	22217	KM17	MB17	28500	32500	5600	125,0	330	260	60	110	24	40	35	230	182	90	83	46	150	83	96	5	M85x2	22	1/2 NPT	1/2 NPT	3/8 BSP	M20	M10	42	63	27,4
90	SOFN 218	22218	KM18	MB18	32500	37500	5300	135,0	360	290	70	120	24	40	45	245	190	95	85	50	160	88	100	5	M90x2	23	1/2 NPT	1/2 NPT	3/8 BSP	M20	M12	45	68	35,7
95	SOFN 219	22219	KM19	MB19	38000	45000	4800	140,0	360	290	80	135	24	40	40	255	210	100	92	53	170	93	105	5	M95x2	24	1/2 NPT	1/2 NPT	3/8 BSP	M20	M12	50	70	33,3
100	SOFN 220	22220	KM20	MB20	42500	49000	4500	145,0	400	320	75	130	28	45	50	270	205	103	93	56	180	98	110	5	M100x2	25	1/2 NPT	1/2 NPT	1/2 NPT	M24	M12	50	70	44,1
110	SOFN 222	22222	KM22	MB22	56000	64000	4000	160,0	420	347	75	145	28	45	50	290	216	115	102	63	200	108	120	5	M110x2	26	1/2 NPT	1/2 NPT	1/2 NPT	M24	M12	50	77	46,1
120	SOFN 224	22224	KM24	MB24	63000	76500	3800	170,0	420	347	90	170	28	45	55	315	245	138	120	74	215	118	135	8	M120x2	28	1/2 NPT	1/2 NPT	1/2 NPT	M24	M16	60	80	67,2
130	SOFN 226	22226	KM26	MB26	73500	93000	3600	180,0	450	377	100	180	28	45	60	335	260	135	120	80	230	128	145	8	M130x2	30	1/2 NPT	1/2 NPT	1/2 NPT	M24	M20	60	85	71,5
140	SOFN 228	22228	KM28	MB28	71000	90000	3200	190,0	500	415	100	190	35	45	65	355	265	140	125	84	250	138	160	8	M140x2	30	1/2 NPT	1/2 NPT	3/4 NPT	M30	M20	60	85	91,5
150	SOFN 230	22230	KM30	MB30	85000	108000	3000	200,0	540	450	115	190	35	50	65	375	265	140	125	89	270	148	170	8	M150x2	32	1/2 NPT	1/2 NPT	3/4 NPT	M30	M20	60	90	104,9
160	SOFN 232	22232	KM32	MB32	100000	129000	2800	215,0	560	470	120	205	35	50	65	405	280	158	140	100	290	158	178	10	M160x2	35	1/2 NPT	1/2 NPT	3/4 NPT	M30	M20	65	95	120,0
170	SOFN 234	22234	KM34	MB34	112000	146000	2600	235,0	610	515	130	230	35	55	70	440	310	175	155	106	310	168	195	10	M170x2	37	1/2 NPT	1/2 NPT	3/4 NPT	M30	M24	75	105	154,0
180	SOFN 236	22236	KM36	MB36	118000	156000	2600	245,0	650	545	150	240	35	65	75	455	320	180	160	106	320	177	205	10	M180x3	38	1/2 NPT	1/2 NPT	3/4 NPT	M30	M24	80	115	176,4
190	SOFN 238	22238	KM38	MB38	127000	170000	2400	260,0	720	590	150	250	42	70	85	480	335	185	165	116	340	188	220	12	M190x3	39	1/2 NPT	1/2 NPT	3/4 NPT	M36	M24	85	120	200,9
200	SOFN 240	22240	KM40	MB40	146000	193000	2200	275,0	730	600	160	260	42	70	85	510	350	189	169	122	360	198	227	12	M200x3	40	1/2 NPT	1/2 NPT	3/4 NPT	M36	M24	85	125	233,2
220	SOFN 244	22244	KM44	MB44	176000	236000	2000	305,0	820	670	180	280	42	80	95	565	370	202	183	132	400	218	255	12	Tr220x4	44	1/2 NPT	1/2 NPT	3/4 NPT	M36	M24	95	140	308,7
240	SOFN 248	22248	KM48	MB48	220000	300000	1800	340,0	900	740	190	290	42	80	100	625	380	210	190	144	440	238	270	12	Tr240x4	47	1/2 NPT	1/2 NPT	3/4 NPT	M36	M24	110	155	367,5