



FCX 00

mancal tipo FLANGE
serviço MÉDIO



Calxa	Eixo		Dimensão nominal (mm)									Paraf.	Peso (kg)		D	Rolamentos			
	Ø pol	Ø mm	a	p	e	i	s	j	k	g	f		UCFCX00	GFCX00		z1	Bi1	z2	Bi2
FCX 05	1	25	111	92,0	65,0	10,0	9,5	6,0	9	24	76,0	M8 5/16	1,10	1,10	62,0	32,2	38,1	40,1	48,3
FCX 06	1-3/16	30	127	105,0	74,2	8,0	12,0	9,5	9	22	85,0	M10 3/8	1,60	1,60	72,0	33,4	42,9	40,3	51,1
FCX 07	1-7/16	35	133	111,0	78,5	9,0	12,0	11,0	11	26	92,0	M10 3/8	2,00	2,00	80,0	39,2	49,2	43,9	56,3
FCX 08	1-1/2 1-9/16	40	133	111,0	78,5	9,0	12,0	11,0	11	26	92,0	M10 3/8	1,90	1,80	85,0	39,2	49,2	43,9	56,3
FCX 09	1-11/16 1-3/4	45	155	130,0	91,9	8,0	14,0	12,0	11	25	108,0	M12 1/2	2,40	2,15	90,0	40,6	51,6	46,1	62,7
FCX 10	1-15/16 2	50	162	136,0	96,2	7,0	14,0	16,0	11	25	118,0	M12 1/2	2,90	2,60	100,0	40,4	55,6	50,6	71,3
FCX 11	2-3/16 2-1/4	55	180	152,0	107,5	4,0	16,0	22,0	13	26	127,0	M14 1/2	4,10	4,30	110,0	43,7	65,1	50,8	77,7
FCX 12	-	60	194	165,0	116,7	11,0	16,0	20,0	14	33	140,0	M14 1/2	5,10	5,610	120,0	50,7	65,1	62,6	85,7
FCX 13	2-7/16 2-1/2	60 65	194	165,0	116,7	11,0	16,0	20,0	14	33	140,0	M14 1/2	5,50	5,70	125,0	55,4	74,6	62,6 55,6	85,7 66,1
FCX 14	2-11/16 2-3/4	65 70	222	190,0	134,3	14,0	19,0	20,0	14	36	164,0	M16 5/8	7,30	7,50	130,0	58,8	77,8	68,8	92,1
FCX 15	2-15/16 3	75	222	190,0	134,3	12,0	19,0	22,0	16	35	164,0	M16 5/8	7,30	7,45	140,0	61,3	82,6	66,8	73,8
FCX 16	3-3/16 3-1/4	80	260	219,0	154,9	10,0	23,0	25,0	19	36	186,0	M20 3/4	11,00	10,80	150,0	61,6	85,7	61,6	85,7
FCX 17	3-7/16	85	260	219,0	154,9	10,0	23,0	25,0	19	36	186,0	M20 3/4	11,10	10,50	160,0	66,3	96,0	56,5	69,5
FCX 18	-	90	260	219,0	154,9	12,0	23,0	28,0	19	43	186,0	M20 3/4	12,00	-	170,0	73,1	104,0	-	-
FCX 20	3-15/16 4	100	276	238,0	168,3	22,0	23,0	28,0	22	66	206,0	M20 3/4	18,40	-	190,0	90,3	117,5	-	-