



SOFN 600

Eixo Ød mm	Mancal	Montagem		Cargas (kgf)		Limite Rotação RPM	Dimensão nominal (mm)																	Roscas			Paraf.	Olhal	C (óleo)		Peso (kg)
		Rolamento	Bucha de Fixação	dinâmica C _r	estática C _{0r}		h	a	e	e1	b	s1	s2	g	w	l	l1	l2	Ca	Da	d1	x	Rg	p1	p2	nível min			nível máx		
45	SOFN 610	22310K	H2310	22000	22400	6300	95,0	270	210	50	92	19	30	30	168	145	75	67,5	46	110	58	3	1/4 NPT	1/4 NPT	3/8 BSP	M16	M10	33	53	20,0	
50	SOFN 611	22311K	H2311	27000	28000	5600	100,0	290	233	50	95	19	33	30	180	148	77,5	70	49	120	65	3	1/4 NPT	1/4 NPT	3/8 BSP	M16	M10	37	53	21,0	
55	SOFN 612	22312K	H2312	31000	33500	5300	110,0	290	230	55	100	19	34	30	198	152	85	77,5	56	130	70	5	1/4 NPT	1/4 NPT	3/8 BSP	M16	M10	40	60	22,0	
60	SOFN 614	22314K	H2314	40000	43000	5600	125,0	330	260	60	110	24	40	35	230	182	90	82,5	61	150	80	5	1/2 NPT	1/2 NPT	3/8 BSP	M20	M10	45	65	28,0	
70	SOFN 616	22316K	H2316	49000	54000	4000	140,0	360	290	80	135	24	40	40	255	210	107	92	68	170	95	5	1/2 NPT	1/2 NPT	3/8 BSP	M20	M12	45	73	34,0	
80	SOFN 618	22318K	H2318	61000	69500	3600	155,0	400	317	95	165	28	45	50	280	246	120	105	74	190	104	5	1/2 NPT	1/2 NPT	1/2 NPT	M24	M12	55	80	44,0	
90	SOFN 620	22320K	H2320	81500	95000	3000	170,0	420	347	90	170	28	45	55	315	245	135	120	89	215	115	8	1/2 NPT	1/2 NPT	1/2 NPT	M24	M16	57	85	68,4	
100	SOFN 622	22322K	H2322	95000	112000	2800	190,0	500	415	100	190	35	45	65	355	265	145	125	96	240	130	8	1/2 NPT	1/2 NPT	3/4 NPT	M30	M20	67	95	93,7	
110	SOFN 624	22324K	H2324	96500	112000	2600	200,0	540	450	115	190	35	50	65	375	265	153	133	102	260	140	8	1/2 NPT	1/2 NPT	3/4 NPT	M30	M20	65	100	107,0	
115	SOFN 626	22326K	H2326	112000	132000	2400	215,0	560	470	120	205	35	50	65	405	285	160	140	109	280	150	8	1/2 NPT	1/2 NPT	3/4 NPT	M30	M20	70	105	122,4	
125	SOFN 628	22328K	H2328	129000	156000	2200	230,0	630	510	120	220	35	60	80	425	300	170	150	118	300	165	8	1/2 NPT	1/2 NPT	3/4 NPT	M30	M24	70	115	155,0	
135	SOFN 630	22330K	H2330	146000	176000	2000	245,0	650	545	150	240	35	65	75	455	320	175	160	128	320	175	10	1/2 NPT	1/2 NPT	3/4 NPT	M30	M24	75	120	180,0	
140	SOFN 632	22332K	H2332	160000	196000	1900	260,0	720	590	150	250	42	70	85	480	335	185	165	134	340	190	10	1/2 NPT	1/2 NPT	3/4 NPT	M36	M24	80	125	205,0	
150	SOFN 634	22334K	H2334	176000	216000	1800	275,0	730	600	160	260	42	70	85	510	350	189	169	144	360	197	12	1/2 NPT	1/2 NPT	3/4 NPT	M36	M24	85	130	238,0	
160	SOFN 636	22336K	H2336	200000	245000	1700	305,0	820	670	180	280	42	80	95	565	370	202	183	150	380	210	12	1/2 NPT	1/2 NPT	3/4 NPT	M36	M24	90	155	315,0	