



CJO 300

mancal tipo FLANGE
serviço PESADO



Caixa	Eixo		Dimensão nominal (mm)						Paraf.	Peso (kg)		D	Rolamentos			
	Ø pol	Ø mm	a	e	i	g	l	s		YCJO3	GCJO3		Y 300		G 300	
												z1	Bi1	z2	Bi2	
CJO 306	1-3/16	30	120	92,1	20,7	14	38	14,5	M12 1/2	2,00	2,10	72,0	46,7	43,0	53,2	50,0
CJO 307	1-1/4 1-7/16	35	130	101,6	21,5	16	40	14,5	M12 1/2	2,40	2,40	80,0	50,5	48,0	54,8	51,6
CJO 308	1-1/2	40	136	104,8	23,0	16	44	16,0	M14 9/16	2,70	2,80	90,0	56,0	52,0	60,3	57,1
CJO 309	1-11/16 1-3/4	45	143	111,1	23,0	17	47	16,0	M14 9/16	3,30	3,50	100,0	58,0	56,0	61,9	58,7
CJO 310	1-7/8 1-15/16	50	165	130,2	27,7	17	53	17,5	M16 5/8	4,80	5,00	110,0	66,7	61,0	69,7	66,6
CJO 311	2 2-3/16	55	178	142,9	31,0	17	58	17,5	M16 5/8	5,80	6,20	120,0	72,0	66,0	76,2	73,0
CJO 312	2-1/4 2-5/16 2-7/16	60 65	190	149,2	35,7	19	65	20,5	M20 3/4	7,10	7,40	130,0	80,7	71,0	84,2	79,4
CJO 314	2-11/16	70	225	177,8	38,9	20	72	24,0	M22 7/8	11,60	12,10	150,0	85,9	78,0	96,9	92,1
CJO 315	2-15/16 3	75	235	184,2	42,1	22	78	24,0	M22 7/8	13,10	14,10	160,0	92,1	82,0	104,8	100,0
CJO 318	3-7/16	90	281	215,9	46,8	28	84	27,0	M24 1	21,10	22,60	190,0	102,8	96,0	119,1	115,9
CJO 320	3-15/16 4	100	316	242,0	54,8	33	97	30,0	M27 1-1/8	30,10	32,00	215,0	120,8	108,0	133,4	128,6